

# Mbsm.pro, Donper, Compressor, R600A, L88CY, 1/5 hp, 1bp

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 23 January 2024

Condor

 **L88CY1**   
220-240V~50Hz 1PH  
THERMALLY PROTECTED   
     
<http://www.donper.com>  
  
220320003580102311

Mbsm.pro, Donper, Compressor, R600A, L88CY, 1/5 hp, 1bp

---

Donper, New, L58CZ1, 220V-240V, 50Hz,  
R134A ,Refrigerator, Compressor,  
1/6++HP, 1/5 hp-, power 116 w, input  
145 w



Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 23 January 2024



L58CZ1

220-240V~50Hz 1PH  
THERMALLY PROTECTED



<http://www.donper.com>



201120003251202363

R134a

SYS12200901

BCD-270 (M)



027002201212000064

Donper, New, L58CZ1, 220V-240V, 50Hz, R134A ,Refrigerator, Compressor, 1/6++HP, 1/5 hp-, power 116 w, input 145 w

---

Mbsm.pro, Freezer, Electrostara, 210 L, ES210ST, Compressor, Donper, L65CZ1, 1/5 hp, 1bp, R134 A, 130 G, 220-244V, 50Hz, 140 w, 1 A, Class T

Category: expertise,Freezer

written by [www.mbsm.pro](http://www.mbsm.pro) | 23 January 2024



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, Freezer, Electrostar, 210 L, ES210ST, Compressor, Donper, L65CZ1, 1/5 hp, lbp, R134 A, 130 G, 220-244V, 50Hz, 140 w, 1 A, Class T

---

# COMPRESSOR, DONPER, NE6213CK, 1/2hp, R404a

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 23 January 2024



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Ne6213Ck Compressor R404A Med Temp 12 Disp 1080W @ -5 1/2Hp 240V 50Hz



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)



**NE6213CK**  
220-240V-50Hz 1PH  
THERMALLY PROTECTED  
RoHS CE ACC088 2  
R404A  
http://www.danfoss.com  
0126741729011801180

# NE6213CK COMPRESSOR R404A MED TEMP 12 DISP 1080W @ -5 1/2HP 240V 50HZ

**Displacement: 12 cm<sup>3</sup>**

**Power: 1/2 HP**

**Oil Charge: 450 +/- 10 mL**

**Cooling capacity: 1080W @-5 SST**

**COP: ASHRAE 1.80**

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Testing condition:

Test conditions	H.B.P	
	ASHRAE	CECOMAF
Evaporating Temp.	+7.2°C	+5°C
Ambient Temp.	+35.0°C	+32°C
Condensing Temp.	+54.4°C	+55°C
Suction Temp.	+35.0°C	+32°C
Subcooling Temp.	+46.1°C	+55°C

### 3. Running Condition

Ambient temp.	0~43°C
Evaporating temp.	-15~10°C
Voltage range	187~264V
Max. condensing temp.	65°C
Max. winding temp.	130°C
Max. shell temp.	95°C
Max. discharge temp.	120°C
Start voltage	187V [5/5bar(abs)]
Shell min. resistance to pressure	35bar

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

## 1. Compressor Type

Compressor model	NE6213CK
Rated voltage/frequency	220-240V~50Hz
Refrigerant	R404A
Application	High back pressure (H.B.P)
Cooling method	Fan Cooling
Start torque	High starting torque (HST)
Control device	Capillary tube
Motor type	CSIR

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm\_dot\_pro\_private\_PDF\_ne6213ck-compressorTélécharger

Refrigeration, Compressor, K270CZ1, 1/3++, DONPER, Dongbei , K325CZ1, K375CZ1 , freezer, R134a, White HIK-BD-500 Chest Freezers, Top Open Door, -18 degrees to +10 degrees, 500L

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 23 January 2024

Product Description

## PRODUCT PARAMETERS

MODEL NO.	K270CY1
COOLING CAPACITY	270W
REFRIGERANTS	R600a
INPUT POWER	208W
HORSE POWER	1/3+
DISPLACEMENT	16.2cm <sup>3</sup>



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Quick Details

Temperature:

-25° ~ +15°

Cooling Capacity:

1ton

Panel Thickness:

50mm

Applicable Industries:

Retail

After Warranty Service:

Online support

Local Service Location:

None

Showroom Location:

None

Condition:

New

Place of Origin:

Hubei, China

Voltage:

220V, 220V/50HZ

Dimension(L\*W\*H):

10-10\*10

Weight:

15KGS

Certification:

CE ROHS

Warranty:

1 Year

After-sales Service Provided:

Online support, No overseas service provided

Key Selling Points:

Sustainable

Machinery Test Report:

Not Availabl

Video outgoing-inspection:  
Provided

Marketing Type:  
New Product 2020

Warranty of core components:  
1 Year

Core Components:  
Motor

Color:  
Black

Product name:  
Refrigerator Compressor

Refrigerant:  
R134a

model:  
K270CZ1

Cooling capacity:  
230W

#### Product Description

<b>Refrigerant</b>	R134a	<b>Cooling capacity</b>	270W
<b>Input power</b>	220W	<b>Input Power</b>	220W
<b>Temperature application</b>	L/MBP	<b>Displacement</b>	9.5cm <sup>3</sup>
<b>Working Current</b>	1.5A	<b>Voltage</b>	220V~240V/50Hz
<b>COP</b>	1.3W/W	<b>Motor type</b>	RSIR
<b>Cylinder capacity</b>	9.5cm <sup>3</sup>	<b>Weight</b>	9.8±0.4kg

Structure



Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO



# PRODUCT PARAMETERS

MODEL NO.	K270CY1
COOLING CAPACITY	270W
REFRIGERANTS	R600a
INPUT POWER	208W
HORSE POWER	1/3+
DISPLACEMENT	16.2cm <sup>3</sup>



Private Picture Copyright : WWW.MBSM.PRO

**Notice :** process channel and air suction pipe can not interchangeable

Product Name : Donper Compressor	Model: K270CZ1
Application : Refrigerator	Power supply :220v~240v/50Hz
Refrigeration capacity:270W	Power :220W
cylinder volume:9.5cm <sup>3</sup>	refrigerant: R134a
Motor :RSIR	COP:1.3W/W
Weight :9.8±0.4kg	working current :1.5A



Private Picture Copyright : WWW.MBSM.PRO

## Compressor Details

Production Name	Refrigerator compressor	Model	K270CZ1
Application	Refrigerator/ Freezer(300L~400L)	Power	220V~240V/50HZ
Cooling capacity	270W	Input power	220W
Cylinder volume	9.5Cm <sup>3</sup>	Refrigerant	R134a
Motor type	RSIR	COP	1.3W/W
Weight	9.8±0.4kg	Current	1.5A

Private Picture Copyright : WWW.MBSM.PRO

## Product Specification

Capacity	500 L
Type	Top Open
Temperature Range	-18 degrees to +10 degrees
Model Number	HIK-BD-500
Model Number/Name	HIK-BD-500

Energy Consumption	2.02 kWh/24hr
Product Dimensions	1650 x 755 x 830mm
Door Type	Top Open Door
Color	White
Door No.	2
Features	Adjustable Temperature Control,Digital Display,75mm Insulation Wall Thickness,Defrost Water Drain
Usage/Application	Freezer/Chiller
Weight	73kg
Depth	755mm
Refrigerant Used	R134a
Number Of Basket	2
Height	830 mm
Power Source	Electric
Energy Efficiency	2.02 kWh/24hr
Compressor Brand	Donper
Compressor Model	K270CZ1
Power	255 W
Width	1650 mm
Colour	White
Refrigerant	R134a
No of Doors	1
Number of Baskets	2

## Product Description

Haikawa now launches its latest range of Chest Freezers in 200 L, 300 L, 400 L and 500 L variants. The freezers come with an Adjustable Temperature Control, enabling its use as a freezer (-18 degrees to 0 degrees) or as a chiller (0 degrees to 10 degrees), depending on requirement. The 75mm Insulation Wall Thickness helps improve energy efficiency, while the unique digital display brings in a whole new level of convenience. The Chest freezers come with removable baskets and a defrost water drain. The Inner PP lining improves hygiene while a lock and key mechanism ensures maximum safety. Insulation: Cyclopentane. Refrigerant: R134a. The HIK-BD-500 model has a rated current of 1.5A, thus lowering the power consumption. The Chest Freezer is packed with the following features:

- Adjustable Temperature Control
- Electronic Controller with Digital Display
- 75mm Insulation Wall Thickness
- Low Power Consumption
- Inner PP Lining for Improved Hygiene
- Store-More Removable Basket
- Defrost Water Drain
- Lid Handle
- Lock and Key Safety Mechanism

# Additional Information

Packaging Details Box Dimensions: 1695 x 760 x 880mm Included: 1 Chest Freezer/ 1 Instruction Manual/ 2 Keys/ 2 Inner Metal Trays



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Compresseur de réfrigérant R134a Donper K375CZ1 220-240V 50Hz SC-SD-388Y

## Description

Compresseur de réfrigérant R134a Donper K375CZ1 220-240V 50Hz SC-SD-388Y

Réfrigérant: R134a

Tension: 220 V ~ 240 V / 50 HZ

Puissance en chevaux: 1/2 ph

Puissance d'entrée: 235 W

Capacité de refroidissement: 325 W

Cylindre de capacité: 11,4 centimètres cubes

Courant de travail: 1.6A

Type de moteur: CSIR

Poids: 9,9 ± 0 4 kg

875000033

 **K375CZ**  
220-240V~50Hz 1PH  
THERMALLY PROTECTED

     1

<http://www.donper.com>  
  
160111104220202452

R134a



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

## COMPRESSEUR, Dongbei, (Donper) ,LBP , S série, S43CZ , 1/7Hp, R134a, RSIR

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 23 January 2024

制冷剂 Refrigerant	应用类型 Application	型号 Model	马力 Power	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	电源 Power Supply	制冷量 Cooling Capacity											COP		启动电容 Run Capacitor	启动电容 Start Capacitor	
								ASHRAE											CECMMF	ASHRAE			CECMMF
								-35	-30	-25	-23.3	-20	-15	-10	-5	0	-25	-23.3					
W	W	W	W	W	W	W	W	W	W	W	W	W	W/W	W/W	μF	μF							
D系列 D Series																							
R134a	LBP	D25CZ	1/4	2.5	S	RSIR	220/50	18	28	42	55	65	86	116	145	182	42	0.95	0.72				
		D30CZ	1/12	3.0	S	RSIR	220/50	25	37	51	66	74	101	136	169	213	50	0.95	0.72				
		D43CZ	1/7	4.3	S	RSIR	220/50	43	66	84	106	114	152	196	250	320	82	1.07	0.81				
		D25BZ	1/10	2.5	S	RSIR	115/60	32	44	57	67	80	100	135	168	214	51	0.95	0.72				
		D30BZ	1/9	3.0	S	RSIR	115/60	36	50	65	72	88	119	150	200	270	55	0.96	0.72				
		D36BZ	1/8	3.6	S	RSIR	115/60	44	65	92	103	109	140	178	228	292	78	1.20	0.91				
直流变频DC Frequency Conversion Range																							
R134a	LBP	W20EZ	1/16	2.0	S	BDM	2-24VDC	28	40	45	56	76	102	130	165	34	1.17	0.89					
		W25EZ	1/14	2.5	S	BDM	2-24VDC	38	57	62	76	100	128	166	210	47	1.15	0.87					
S系列 S Series																							
R134a	LBP	S30CZ	1/12	3.0	S	RSIR	220/50	26	39	53	66	76	102	138	188	232	50	0.95	0.72				
		S36CZ	1/8	3.6	S	RSIR	220/50	35	53	75	90	104	139	180	242	307	68	1.05	0.80				
		S43CZ	1/7	4.3	S	RSIR	220/50	43	66	84	106	114	152	196	250	320	81	1.07	0.81				
		S53CZ	1/6-	5.3	S	RSIR	220/50	46	72	106	118	145	195	246	320	388	90	1.15	0.87				
		S30BZ	1/10	3.0	S	RSIR	115/60	36	50	65	72	88	119	150	200	270	55	0.96	0.73				
		S36BZ	1/7	3.6	S	RSIR	115/60	44	65	92	103	109	140	178	228	292	78	1.10	0.84				
		S43BZ	1/6-	4.3	S	RSIR	115/60	48	74	108	125	150	206	270	336	412	95	1.16	0.88				
		S53BZ	1/6+	5.3	S	RSIR	115/60	50	90	131	145	172	226	300	380	468	110	1.18	0.90				
		SK30CZ	1/10	3.0	S	RSCR	220/50	36	55	74	80	98	132	166			61	1.25	0.95	4			
		SK36CZ	1/8	3.6	S	RSCR	220/50	40	62	86	95	114	158	206			72	1.25	0.95	4			
		SK43CZ	1/6-	4.3	S	RSCR	220/50	46	71	95	115	143	190	245			87	1.30	0.99	4			
		SK53CZ	1/6	5.3	S	RSCR	220/50	48	79	116	130	153	200	260			99	1.30	0.99	4			
		SK30BZ	1/8	3.0	S	RSCR	115/60	40	62	84	95	114	158	200			72	1.25	0.95	12			
		SK36BZ	1/6-	3.6	S	RSCR	115/60	47	73	98	120	138	188	250			91	1.30	0.99	12			
		SK43BZ	1/6	4.3	S	RSCR	115/60	52	82	120	140	168	221	293			106	1.35	1.03	12			
SK53BZ	1/5	5.3	S	RSCR	115/60	55	95	138	158	180	237	304			120	1.35	1.03	12					



Private Picture Copyright: WWW.MBSM.PRO

COMPRESSEUR, Dongbei, (Donper) ,LBP , S série, S43CZ , 1/7Hp, R134a, RSIR

L76CZ1, Donper, R134A, 220W, 220-240V/50-60HZ, 1Phase, 1/4 Hp, (+BIg = 1/3-Hp), compressor, Hermetic, refrigerator, RSIR, oil 250 ML

Category: compressor

written by www.mbsm.pro | 23 January 2024

Model	Application	Power supply	Refrigeration capacity	Power	Cylinder volume	Refrigerant	Motor	COP:	Weight	Working current
K230CZ1	Refrigerator	220v~240v /50Hz	230W	220W	8.3cm <sup>3</sup>	R134a	RSIR	1.3W/W	9.7 ± 0.4kg	1.35A
K270CZ1	Refrigerator	220v~240v /50Hz	270W	220W	9.5cm <sup>3</sup>	R134a	RSIR	1.3W/W	9.8 ± 0.4kg	1.5A
K325CZ1	Refrigerator	220v~240v /50Hz	325W	235W	11.4cm <sup>3</sup>	R134a	CSIR	1.3W/W	9.9 ± 0.4kg	1.6A
K375CZ1	Refrigerator	220v~240v /50Hz	375W	310W	12.7cm <sup>3</sup>	R134a	CSIR	1.3W/W	9.9 ± 0.4kg	2.1A
L58CZ1	Refrigerator	220v~240v /50Hz	150W	120W	5.8cm <sup>3</sup>	R134a	RSIR	1.3W/W	7.8 ± 0.4kg	0.85A
L65CZ1	Refrigerator(200L~320L)	220v~240v /50Hz	170W	136W	6.5cm <sup>3</sup>	R134a	:RSIR	1.25W/W	8.2 ± 0.4kg	1.15A
L72CZ1	Refrigerator(200L~370L)	220v~240v /50Hz	195W	150W	7.2cm <sup>3</sup>	R134a	RSIR	1.3W/W	9.1 ± 0.4kg	1.04A
L76CZ1	Refrigerator(280L~360L)	220v~240v /50Hz	220W	170W	7.6cm <sup>3</sup>	R134a	RSIR	1.32W/W	8.9 ± 0.4kg	1.4A
NE5165CZ	Refrigerator(1000L~2000L)	220v~240v /50Hz	850W	380W	9cm <sup>3</sup>	R134a	RSIR	2.1W/W	11 ± 0.5kg	2.3A
NE6188CZ	Refrigerator(1000L~2000L)	220v~240v /50Hz	860W	410W	12.1cm <sup>3</sup>	R134a	CSIR	2.0W/W	11 ± 0.5kg	2.6A
NE6210CZ	Refrigerator(1000L~2000L)	220v~240v /50Hz	1050W	500W	14.2cm <sup>3</sup>	R134a	CSIR	2.1W/W	11.2 ± 0.5kg	3.5A

Private Picture Copyright : WWW.MBSM.PRO

L76CZ1, Donper, R134A, refrigerator, RSIR, 220W, 1/4 Hp, (+BIg), (1/3- HP), compressor, High Pressure, High Pressure ,