

Huayi HYE69Y63 Compressor 1/5 HP R134a LBP

Category: Refrigeration

written by www.mbsm.pro | 18 January 2026



Private Picture Copyright : WWW.MBSM.PRO

The Huayi HYE69Y63 is a highly efficient hermetic reciprocating compressor designed for low back pressure applications using R134a refrigerant. With a 1/5 HP rating and dual-frequency compatibility (50/60Hz), this motor is a cornerstone for domestic refrigerators and freezers. This comprehensive guide covers technical datasheets, electrical wiring, and professional replacement strategies for global cooling systems.

GMCC PE75H1C Compressor 1/4 HP R134a LBP

Category: Refrigeration

written by www.mbsm.pro | 18 January 2026



Private Picture Copyright : WWW.MBSM.PRO

The GMCC PE75H1C is a robust hermetic reciprocating compressor engineered for low back pressure applications using R134a refrigerant. Operating at 220-240V 50Hz, this 1/4 HP motor provides a cooling capacity of approximately 185W. This article provides technical datasheets, electrical wiring schemas, and professional cross-reference guides for global refrigeration maintenance and engineering.

TEE NTU 170 MT Compressor 1/4 HP R600a

Category: Refrigeration

written by www.mbsm.pro | 18 January 2026



Private Picture Copyright : WWW.MBSM.PRO

The TEE NTU 170 MT is a high-efficiency hermetic reciprocating compressor designed for low back pressure applications using R600a refrigerant. Known for its reliability in household refrigeration, this unit operates at 220-240V 50Hz. This article explores its technical specs, cooling capacity, and suitable replacements for HVAC technicians and engineers worldwide.

Compressor, r600a, 1/5HP, LBP, 149W, htk12aa, Electrolux, Brandt, 220-240V 50Hz, Run Capacitor: 4.0 μ F (5.0 μ F as alternative) , Motor type RSCR/RSIR

Category: compressor

written by www.mbsm.pro | 18 January 2026



Private Picture Copyright : WWW.MBSM.PRO

compressor/compressor ACC – Electrolux HTK12AA, LBP – R600a, Power consumption 1/5HP++, 220-240V/1/50Hz, Motor type RSIR, Injection: Capillary operation, Displacement 11.1 cm³, Oil type mineral oil, Oil quantity 170 cm³, Power 116 W at -25 / +55°C, Power consumption 149 W, Current 0.77, Weight 8.6 Cooling capacity

-10 °C	-15 °C	-20 °C	-25 °C	-30 °C	-35 °C
300	240	188	144	107	78

Shipping Class	Standard
Scope Of Application	LBP
Lieferzeit	2-3 Wochen
Type Of Construction	Piston
Condensation Temperature	55°C

Maker	ACC
Manufacturer No.	HPY12AA
Displacement In Cm3	11.1
Measuring Requirements	Ashrae
Refrigerants	R600a
Series	HPY
Condensing Units Compressors	Compressors
Suspense	220-240V
Weight In Kg	12.7

1. Be the first to review this product

[Mbsm_dot_pro_private_PDF_HTK12AA-1-1Télécharger](#)

[Mbsm_dot_pro_private_PDF_HTK12aa-1Télécharger](#)



Verdichter - Cubigel

R-600a, LBP

Hermetische Verdichter für Kapillarrohrbetrieb.
Hochleistungs-Verdichter mit Betriebskondensatoren.
LBP Temperaturbereich -30 °C bis -10 °C.
Netzspannung 220 - 240 V / 50 Hz.



Artikelnr.	Typ	Leistung (PS)	Kälteleistung [W] T_e -25 °C, T_k +45 °C	
				-25
47-32 HQY45AA	HQY 45 AA	1/12		52
47-32 HQY55AA	HQY 55 AA	1/9		62
47-32 HQY70AA	HQY 70 AA	1/8		80
47-32 HQY80AA	HQY 80 AA	1/7		99
47-32 HQY90AA	HQY 90 AA	1/7		109
47-32 HQY99AA	HQY 99 AA	1/6		119
47-32 HPY12AA	HPY 12 AA	1/5		144
47-32 HPY14AA	HPY 14 AA	1/5		166
47-32 HPY16AA	HPY 16 AA	1/4		181

Gesamtkatalog jetzt anfordern unter info@kaeltepartner.net!

 **Hinweis: Bilder Können vom Produkt abweichen**

Private Picture Copyright: WWW.MBSM.PRO