Compressor, FLB075LBNA, LG-Original New Linear Refrigerator Compressor, LG-compresor, Inverter 0~220V 53Hz, R134a(165g), LSXC22386, LSXC22326, LSXC22336, 1/4HP

Category: compressor
written by www.mbsm.pro | 17 October 2021



Private Picture Copyright : WWW.MBSM.PRO

FLS075LANA is the new **compressor** model number It replaces these older **LG**/Kenmore Elite **compressor** versions: FC75LBNA FLA075LANA FLB075LANA **FLB075LBNA**
Compressor Fls075lana_replacement A: Fla075lana, Flb075lana
Compressor, FLB075LBNA, LG-Original New Linear Refrigerator Compressor, LG-compresor, Inverter 0~220V 53Hz, R134a(165g), LSXC22386, LSXC22326, LSXC22336, 1/4HP
New version LG Compressor part # TCA38091801 & Software Jig TCA35911910
Compressor has a purple decal and red decal on top warning about the software update.
FLS075LANA is the new compressor model number
It replaces these older LG/Kenmore Elite compressor versions:
FC75LBNA
FLA075LANA
FLB075LANA
FLB075LBNA



Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO




Private Picture Copyright : WWW.MBSM.PRO



Name Plate




Size : 90mm X 20mm



Private Picture Copyright : WWW.MBSM.PRO

Compressor Label



Private Picture Copyright : WWW.MBSM.PRO

Defrost	End		Auto
	Evaporation		Forced method
	Type of heat shield		Cyclo-Pentane
F-Room	Fixed Shelf		3
	Drawer		2
R-Room	Fixed Shelf		4
	Shelf(Movable, Folding)		-
	Egg container		-
	Vegetable room		2
Freezing cycle	Compressor driving method		A Logic Inverter operation
	Evaporation		Pin tube type
	Conderser		Forced convection method
	F-Room oil		Freol Alpha5 oil(175cc)
	Type of refrigerant		R134a(165g)
	Capillary tube		Φ 0.7/0.9
	Dryer (drying tube)		MOLECULAR SIEVE XH-9
Electrical parts		Initial defrost	4~5 hours (vary depending on condition)
		Defrost cycle	9~11 hours (vary depending on condition)
		Rest time	3 Min
		Defrost sensor	Returend to defrost function when reaching to 5℃
		Temp.fuse (rated/ operation temperature)	250V / 72℃
		Heater Sheath	AC 115V / 260W
	Parts related with dewing prevention	Dispenser duct door heater	-
		R-Room home bar heater	120V / 6.5W
		F-Room home bar heater	-
		Dispenser heater	DC 12V / 2.5W
	Capacitor	Comp' Running	AC 450V / 20 ㎌
		I/maker geared motor Running	AC 250V / 14 ㎌

Private Picture Copyright : WWW.MBSM.PRO