



Compressor, Embraco, EMX20CLC, High-quality, compressor Aspera, EMX20CLC, LBP R600a, 220-240V 50Hz, 3.97 cm³, 1/12HP

Category: compressor

written by www.mbsm.pro | 15 December 2021

Model EMX20CLC Code 513309529...S		embraco POWER IN. CHANGE ON.
220V 60 1~		GENERAL DATA Application: LBP Refrigerant: R600a Evaporating Temperature Range: -35°C to -10°C Compressor Cooling: Static Type: Hermetic reciprocating Technology Type: On-Off Expansion Device: Capillary Tube Packing Quantity: 100 Displacement: 3.97 cm ³ Horse power: 1/12 hp Approvals:
MECHANICAL DATA Bore: 19 mm Stroke: 14 mm Oil Charge: 180ml Oil Type Configuration: ALQUILB Oil Type Viscosity: IS05 Weight: 7.88 kg		 ELECTRICAL DATA Motor Type: RSCR Starting Torque: LST Voltage working range at 50 Hz: 198-242 V Voltage working range at 60 Hz: 198-242 V Maximum Motor Temperature: 130 °C Start Winding Resistance: 22.1 Ω (± 10%) at 25°C Run Winding Resistance: 50.65 Ω (± 10%) at 25°C

Private Picture Copyright: WWW.MBSM.PRO

GENERAL DATA

Application: LBP
Refrigerant: R600a
Evaporating Temperature Range: -35°C to -10°C
Compressor Cooling: Static
Type: Hermetic reciprocating
Technology Type: On-Off
Expansion Device: Capillary Tube
Packing Quantity: 100
Displacement: 3.97 cm³
Horse power: 1/12 hp
Approvals:



MECHANICAL DATA

Bore: 19 mm
Stroke: 14 mm
Oil Charge: 180ml
Oil Type Configuration: ALQUILB
Oil Type Viscosity: IS05
Weight: 7.88 kg

ELECTRICAL DATA

Motor Type: RSCR
Starting Torque: LST
Voltage working range at 50 Hz: 198-242 V

Voltage working range at 60 Hz: 198-242 V
 Maximum Motor Temperature: 130 °C
 Start Winding Resistance: 22.1 Ω (± 10%) at 25°C
 Run Winding Resistance: 50.65 Ω (± 10%) at 25°C

<p>Model EMX20CLC Code 513309529...S</p> <p>220V 60 1~</p>  <p>MECHANICAL DATA</p> <p>Bore: 19 mm Stroke: 14 mm Oil Charge: 180ml Oil Type Configuration: ALQUILB Oil Type Viscosity: ISO5 Weight: 7.88 kg</p>	<p style="text-align: right;">embraco POWER IN. CHANGE ON.</p> <p>GENERAL DATA</p> <p>Application: LBP Refrigerant: R600a Evaporating Temperature Range: -35°C to -10°C Compressor Cooling: Static Type: Hermetic reciprocating Technology Type: On-Off Expansion Device: Capillary Tube Packing Quantity: 100 Displacement: 3.97 cm³ Horse power: 1/12 hp Approvals:</p> <p>ELECTRICAL DATA</p> <p>Motor Type: RSCR Starting Torque: LST Voltage working range at 50 Hz: 198-242 V Voltage working range at 60 Hz: 198-242 V Maximum Motor Temperature: 130 °C Start Winding Resistance: 22.1 Ω (± 10%) at 25°C Run Winding Resistance: 50.65 Ω (± 10%) at 25°C</p> 
--	--

Private Picture Copyright: WWW.MBSM.PRO



Private Picture Copyright: WWW.MBSM.PRO