

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP , 1PH , 220-240 V 50 Hz

written by Jamila | 1 October 2018

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP ,
1PH , 220-240 V 50 Hz



PictureS Mbsm Dot Pro : www.mbsm.pro

- Puissance en cheval 1/6 CV
- Cylindrée 5.99 cm³
- 220-240 V 50 Hz
- Gaz R134a LBP
- Température d'utilisation max. 32°C
- Avec boîtier et système de démarrage

La photo montre l'aspect du compresseur, pas son étiquette réelle

Codes fabricants

- ACC-GL60AA
- ACC-GL60AB
- ACC-GL60AH
- CUBIGEL-GL60AA
- CUBIGEL-GL60AB
- CUBIGEL-GL60AH
- MONDIAL ELITE-4106004
- MONDIAL ELITE-1147031
- Embraco Aspera- B1112Z





PictureS Mbsm Dot Pro : www.mbsm.pro



PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm_dot_pro_private_PDF_GL60AATélécharger
Mbsm_dot_pro_private_PDF_-GL60AATélécharger



Type: Hermetic piston compressors**Producer:** ACC**Series:** HMBP
Model: GL60AA
General data

Refrigerant:	R134a	
Discharge element:	C	
Cooling:	S	
Maximum ambient temperature [°C]:	43	

Compressor's data

Cylinder capacity [cm³]:	6	
Displacement [m³/h]:	1	
Weight [kg]:	9,1	
Oil charge [cm³]:	265	
Oil type:	ISO VG 19 ESTER	

Engine's data

Engine type:	RSIR	
Power [KM]:	1/6	
Starting element:	LST	
Power supply:	220V 50Hz	
Voltage range:	187-264	
Locked rotor current [A]:	9,9	
Running winding resistance (25°C) [Ω]:	15,6	
Starting winding resistance (25°C) [Ω]:	21,31	

Electrical data

Relays:	3003	
Shielding element:	MRA38028, T0508, AF18FU	
Starting capacitor volume [μF]:		

Connections

	millimeters	inches	
Suction tube:	6,5		
Service tube:	6,5		

Discharge tube:	4,9		
-----------------	-----	--	--