Resin Pack ,Brushless ,Dc motor , Gangdomg ,Welling Motor Manufacturing ,CO.,LTD. ,DC280v ,20w , 0.10a ECL ,8P 1300r/min

Category: Solutions,Technologie,Tester ok
written by www.mbsm.pro | 8 January 2019



Resin Pack ,Brushless ,Dc motor , Gangdomg ,Welling Motor Manufacturing ,CO.,LTD. ,DC280v ,20w , 0.10a ECL ,8P 1300r/min

---

MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co., Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

Category: Solutions,Tester ok
written by Jamila | 8 January 2019



MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co., Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

Test conditions	According to ASHRAE
Evaporating temperature	-23.3□
Condensing temperature	54.4□
Subcooling temperature	32.2□
Suction temperature	32.2□
Ambient temperature	32.2□
Working condition limit:R134a	
Max ambient temperature	43[□]
Evaporation temperature range	-35~-15[□]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0[Mpa](gauge pressure)
Max allowable housing temperature	95[□]
Max discharge temperature	125[□]
Max pressure housing endured	2.7[Mpa](gauge pressure)
Low voltage start	0.4/0.4Mpa(gauge pressure)187V/98V

Product model:HYE69YL
Cooling capacity:195W
COP□W/W□:1.15
Voltage□V□:220-240~
Frequency(Hz):50



PictureS Mbsm Dot Pro : www.mbsm.pro

- Products
- R134a Compressor (LBP)
  - HYE Serie
  - HY Serie
  - HYB Serie
  - HYS Serie
- R600a Compressor (LBP)
  - HYE Serie
  - HY Serie
  - HYB Serie
  - HYS Serie
- R134a Compressor (MBP,HBP)
  - HY Serie
  - HYE Serie
- Newest Catalog Download

www.mbsm.pro



Product model:HYE69YL
Cooling capacity:195W
COP（W/W）:1.15
Voltage（V）:220-240~
Frequency(Hz):50

Test conditions	According to ASHRAE
Evaporating temperature	-23.3℃
Condensing temperature	54.4℃
Subcooling temperature	32.2℃
Suction temperature	32.2℃
Ambient temperature	32.2℃
Working condition limit:R134a	
Max ambient temperature	43[℃]
Evaporation temperature range	-35~-15[℃]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0[Mpa](gauge pressure)
Max allowable housing temperature	95[℃]
Max discharge temperature	125[℃]
Max pressure housing endured	2.7[Mpa](gauge pressure)
Low voltage start	0.4\0.4Mpa(gauge pressure)187V/98V

PictureS Mbsm Dot Pro : www.mbsm.pro



AE 1330 Y

1 / 12 HP



AE 1340 Y

1 / 6 HP



AE 1350 Y

1 / 6 HP

www.mbsm.pro



AE 1360 Y

1 / 5 HP



AE 1370 Y

1 / 4 HP



AE 1390 Y

1 / 4 HP

PictureS Mbsm Dot Pro : www.mbsm.pro



HY 81 Y

1 / 4 HP



HYE 55 YL 63

1 / 6 HP



HYE 60 YL 63

1 / 5 HP



HYE 69 YL

1 / 4 HP



HYE 125 MSU

1 / 4 HP

www.mbsm.pro

PictureS Mbsm Dot Pro : www.mbsm.pro

Huayi HYE 69 YL 1/4 Hp 168Kcal R134a 220V

Huayi - Huayi

Huayi HYE 55 YL 63 1/6 Hp 129Kcal R134a 220V

Huayi - Huayi

Huayi HYE 60 YL 63 1/5 Hp 146Kcal R134a 220V

Huayi - Huayi

Huavi HY 81 Y 1/4+ Hp 202Kcal R134a 220V

PictureS Mbsm Dot Pro : www.mbsm.pro

HYE 125 MSU

HYE 69 YL

HYE 60 YL 63

HYE 55 YL 63

HY 81 Y

AE 1390 Y

AE 1370 Y

AE 1360 Y

AE 1350 Y

AE 1340 Y

AE 1330 Y

PictureS Mbsm Dot Pro : www.mbsm.pro



Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO