

Mbsm.pro, Refrigerator, No frost,
Made in Egypt, Ideal, 340NSL008,
2008, 338 L, compressor , 1/4 hp,
HPL27YE – 5-K, r134a, 125 G,198 w,
LBP

Category: compressor,Refrigerator

written by www.mbsm.pro | 8 January 2024



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Refrigerator, No frost, Made in Egypt, Ideal, 340NSL008, 2008, 338 L, compressor , 1/4 hp, HPL27YE – 5-K, r134a, 125 G,198 w, LBP

Certificate, ZMC, zanussi, Made in Egypt, Compressor, EGM90AZ, 1/4 hp, Lbp, R134a

Category: compressor

written by Amina | 8 January 2024



Private Picture Copyright : WWW.MBSM.PRO

Certificate, ZMC, zanussi, Made in Egypt, Compressor, EGM90AZ, 1/4 hp, Lbp, R134a

Mbsm.pro, Ideal, Refrigerator, 268 L,
141 w, Es:320-2005, 2000nf, made in
Egypt, Compressor, 1/5 hp, G160tb,
egm75af, r134a, 105 g

Category: compressor

written by www.mbsm.pro | 8 January 2024



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Ideal, Refrigerator, 268 L, 141 w, Es:320-2005, 2000nf, made in Egypt,
Compressor, 1/5 hp, G160tb, egm75af, r134a, 105 g

ZMC, zanussi, Made in Egypt, Compressors

Category: compressor

written by www.mbsm.pro | 8 January 2024

R134a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
▶ <input type="checkbox"/> GL45AA	LBP::R134a	1/8	43	A	96	82	1.06	0.82		
▶ <input type="checkbox"/> GL45AN	LBP::R134a	1/8	50	C	96	81	1.05	0.8		
▶ <input type="checkbox"/> GL60AA	LBP::R134a	1/6	43	A	132	114	1.14	0.89		
▶ <input type="checkbox"/> GL60AF	LBP::R134a	1/6	43	D	132	113	1.07	0.82		
▶ <input type="checkbox"/> GL60AH	LBP::R134a	1/6	43	A	133	114	1.31	1.01		
▶ <input type="checkbox"/> GL60AN	LBP::R134a	1/6	50	C	132	114	1.07	0.83		
▶ <input type="checkbox"/> GL70AA	LBP::R134a	1/5	43	A	149	128	1.18	0.92		
▶ <input type="checkbox"/> GL70AN	LBP::R134a	1/5	50	D	150	129	1.08	0.83		
▶ <input type="checkbox"/> GL70AT	LBP::R134a	1/5	43	E	144	122	1.09	0.84		
▶ <input type="checkbox"/> GL75AA	LBP::R134a	1/5	43	A	155	133	1.18	0.92		
▶ <input type="checkbox"/> GL80AA	LBP::R134a	1/5	43	A	173	148	1.19	0.93		
▶ <input type="checkbox"/> GL80AF	LBP::R134a	1/5	43	D	166	141	1.14	0.88		
▶ <input type="checkbox"/> GL80AH	LBP::R134a	1/5	43	A	175	150	1.35	1.06		
▶ <input type="checkbox"/> GL80AN	LBP::R134a	1/4	43	A	196	168	1.36	1.06		
▶ <input type="checkbox"/> GL90AA	LBP::R134a	1/4	43	A	195	167	1.19	0.93		
▶ <input type="checkbox"/> GL90AH	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
▶ <input type="checkbox"/> GL90AN	LBP::R134a	1/4	50	D	190	163	1.1	0.85		
▶ <input type="checkbox"/> GL90AT	LBP::R134a	1/4	43	E	190	161	1.19	0.92		
▶ <input type="checkbox"/> GL99AA	LBP::R134a	1/4	43	A	214	182	1.24	0.96		
▶ <input type="checkbox"/> GL99AH	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
▶ <input type="checkbox"/> GL80AD	LBP::R134a	1/5	43	W	0	0	0	0		
▶ <input type="checkbox"/> GL90AD	LBP::R134a	1/4	43	W	0	0	0	0		

R12

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
▶ <input type="checkbox"/> L45AV	LBP::R12	1/8	43	B	221	192	0.91	0.71		
▶ <input type="checkbox"/> L55AV	LBP::R12	1/6	43	B	115	101	0.99	0.78		
▶ <input type="checkbox"/> L55BV	LBP::R12	1/6	43	B	115	101	0.99	0.78		
▶ <input type="checkbox"/> L76AV	LBP::R12	1/5	43	B	145	127	1.05	0.84		
▶ <input type="checkbox"/> L76BV	LBP::R12	1/5	43	B	145	127	1.05	0.84		
▶ <input type="checkbox"/> L88AV	LBP::R12	1/4	43	B	171	150	1.02	0.81		
▶ <input type="checkbox"/> L88BV	LBP::R12	1/4	43	B	171	150	1.02	0.81		
▶ <input type="checkbox"/> LT45AV	LBP::R12	1/8	50	B	94	83	1.04	0.83		
▶ <input type="checkbox"/> LT55AV	LBP::R12	1/6	50	B	115	102	1.06	0.85		
▶ <input type="checkbox"/> LT55BV	LBP::R12	1/6	50	B	115	102	1.06	0.85		
▶ <input type="checkbox"/> LT76BV	LBP::R12	1/5	50	B	155	137	1.14	0.91		
▶ <input type="checkbox"/> LT88BV	LBP::R12	1/4	50	B	190	169	1.16	0.93		
▶ <input type="checkbox"/> P12BW	LBP::R12	1/3	43	A	221	192	0.91	0.71		

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_catalogo_cubigel_R134aTélécharger

R600a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
▶ <input type="checkbox"/> HL80AH	LBP::R600a	1/7	43	A	104	89	1.37	1.06		
▶ <input type="checkbox"/> HL90AH	LBP::R600a	1/7	43	A	115	99	1.38	1.08		
▶ <input type="checkbox"/> HL99AH	LBP::R600a	1/6	43	A	120	103	1.34	1.03		

Private Picture Copyright : WWW.MBSM.PRO

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP _a
					CECOMAF	ASHRAE	
					5°C W	7.2°C kcal/h	
▶ <input type="checkbox"/> GL45PB	HMBP::R134a	1/6	43	A			
▶ <input type="checkbox"/> GL45PB	HMBP::R134a	1/6	0	300			
▶ <input type="checkbox"/> GL45TB	HMBP::R134a	1/6	43	A			
▶ <input type="checkbox"/> GL60PB	HMBP::R134a	1/5	43	A			
▶ <input type="checkbox"/> GL60TB	HMBP::R134a	1/5	43	A			
▶ <input type="checkbox"/> GL80PB	HMBP::R134a	1/5	43	A			
▶ <input type="checkbox"/> GL80TB	HMBP::R134a	F	0	300			
▶ <input type="checkbox"/> GL90TB	HMBP::R134a	1/4	43	A			
▶ <input type="checkbox"/> GP12TB	HMBP::R134a	3/8	43	A			

Private Picture Copyright : WWW.MBSM.PRO

ZMC, zanussi, Made in Egypt,
Compressor, Frost Free Freezer,
GM90AZ, EGM90AZ, 155W, 1/5Hp, 134A,
150G, Electrostar Freezer, 260L
CRoss, 235L Storage , 220v-50H, 1.2A,
Class T

Category: compressor

written by www.mbsm.pro | 8 January 2024

COMPRESSOR TECHNICAL DATA

General Data

Refrigerant:	R134a
Application:	LBP
Evaporating Temperature Range:	-30°C to -10°C
Voltage/Frequency:	220/240V/50 HZ
Compressor Cooling:	Static
Expansion Device:	Capillary Tube
Packaging Quantity:	Multi – 96:120 pcs
Approvals:	CE-VDE-GOST

Mechanical Data

Oil Charge:	300 cm3
Oil Type Configuration:	ester

Oil Type Viscosity: 19 cSt
Weight: 10 kg

Electrical Data

Motor Type: RSIR / RSCR*
Voltage working range at 50 Hz: 187-264V
Maximum Motor Temperature: 130°C
Locked Rotor Current: 14.46 / 9.86 A
Start Winding Resistance: 23.40Ω at 25°C
Run Winding Resistance: 8.08 Ω at 25°C
Phase: 1 ph

External Characteristics


Internal Diameter (mm)
Suction Connector 6.5
Discharge Connector 4.9
Process Connector 6.5
Material Copper

Electrical Components

Starting Device: PTC 14Ω
Motor Protection: T0490/xx



OO HUAWEI NOVA 5T
OO AI QUAD CAMERA



Made In Egypt

Frost Free Freezer

Model **ES 260 NF** طراز

Voltage **220 V - 50 HZ 1.2A 155 W**

Freezing Capacity 22 Kg/24Hr

Freezer Stopage Volume 235 Lit.

Total Gross Volume 260 Lit

Refrig. Storage Volume



024287

R134a **150g** وزن وسيط

التبريد

Class T صنع في مصر

max. lamp input

Without

15 W

Protection Rating

IPX 4

According To

ES 6000 / 2008 - ISO 15502 / 2005

OO HUAWEI nova 5T
OO AI QUAD CAMERA

Private Picture Copyright: WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_EGM90AZTélécharger