Whirlpool, Aspera, NE2125E, LBP, capacitive, start inductive run, hermetic compressor, R22, 1/4Hp++ or 1/3Hp–

Category: compressor
written by www.mbsm.pro | 18 March 2021
ompressor Aspera NE2125E, LBP – R22, 220-240V / 1 / 50Hz, stroke volume 8.78 cm3, LRA 11.0A, motor type CSIR, capillary tube / expansion valve operation, oil AB 46.Cooling
capacity measured for condensation temperature of: 45 ° C, Measurement conditions: ASHRAE
Unfortunately the compressor is no longer available.
If you would like an offer for an identical alternative, please email us or give us a short call, we will prepare an offer for you.Cooling capacity (W) at To

– 10 ° C	– 15 ° C	– 20 ° C	– 25 ° C	– 30 ° C
651	517	401	304	226



Private Picture Copyright : WWW.MBSM.PRO

R22 - LBP Applications			
COMPRESSOR	FREQUENCY	DIMENSION (from –30°C to –5°C evap. temp.)	–
NE2125E	50 Hz	0.91 mm I.D. x 3.2 m	–
	60 Hz	0.91 mm I.D. x 2.85 m	–
NE2134E	50 Hz	0.91 mm I.D. x 2.8 m	–
	60 Hz	0.91 mm I.D. x 2.5 m	–
T2140E	50 Hz	0.91 mm I.D. x 2.6 m	–
	60 Hz	0.91 mm I.D. x 2.3 m	–
T2155E	50 Hz	1.20 mm I.D. x 3.9 m	–
	60 Hz	1.20 mm I.D. x 3.5 m	–
T2168E	50 Hz	1.20 mm I.D. x 3.3 m	–
	60 Hz	1.20 mm I.D. x 2.8 m	–
NJ2178E	50 Hz	1.20 mm I.D. x 3.0 m	–

PictureS Mbsm Dot Pro : www.mbsm.pro
Private Picture Copyright : WWW.MBSM.PRO

Private Picture Copyright : WWW.MBSM.PRO

Private Picture Copyright : WWW.MBSM.PRO

Private Picture Copyright : WWW.MBSM.PRO

Private Picture Copyright : WWW.MBSM.PRO

Private Picture Copyright : WWW.MBSM.PRO

Private Picture Copyright : WWW.MBSM.PRO

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_ne2125e-Embraco_VerdichterTélécharger

Shipping Class	Default
Scope Of Application	LBP
Delivery Time	2-3 Weeks
Stock Availability	In Stock
Type	Reciprocating Piston
Condensation Temperature	45 ° C
Manufacturer	Aspera
Manufacturer No.	NE2125E
Power In Hp	1/4 +
Starting Torque	HST
Stroke Volume In Cm3	8.78
Measurement Conditions	Ashrae
Refrigerant	R22
Oil Type	ISO46
Series	NE
Condensing Units Compressors	Compressor

Tension	220-240V
Weight In Kg	10.4