

MBSM.pro, Compressor, 13HP, Danfoss, Performer, Scroll Compressor, Sm160, Sm161t4vc, Refrigeration Chiller, 3 ph, 380 v, 38BB 055 – 240, 38bb-250 9e/k, 38BB 250, 250 = 250000 kBtu/hr, 30 Ton, r22, 19 Kg, suction 1-1/8"–2, refoulement 5/8"–2

Category: Archivation,compressor

written by www.mbsm.pro | 19 April 2022

Danfoss
MADE IN CHINA

Model no: **SM161T4VC**



Serial no: **GD2503110072**



M 380-400 V 3 ~ 50 Hz
460 V 3 ~ 60 Hz
LR 145 A MAX OPER. 31 A
Thermally protected system
P.E.D. LP side HP side
Marking 25 bar 27.8 bar
PS 63 °C 150 °C
TS max -35 °C -35 °C
TS min 17.6 L 20 L
Volume 17.6 L 20 L
Lubricant: MINERAL OIL 160P

CE ENEC
0062



2016 Refrigerant: R22 (UL rating) - R417A with 160S2
PROTECTED BY DOMESTIC AND FOREIGN PATENTS

WARNING

Installation and servicing shall be performed by trained personnel only. Failure to observe these safety warnings could result in serious injury or death.
ELECTRIC SHOCK HAZARD: Turn off power before servicing. Disconnect all conductors.
Keep terminal cover in place and properly secured. Refrigerant power is applied to the compressor and the refrigerant unit is grounded system only.
HIGH PRESSURE: System contains refrigerant and oil under pressure. Pressure increases from both the high and low side during servicing when safety devices.
FIRE HAZARD: Use tubing cutter to remove refrigerant. Do not use torch or hot metal parts.



CAUTION
Use only manufacturer's recommended oil and refrigerant. Do not mix. Use only manufacturer's recommended tools and equipment. Do not use open flame. Do not use electrical equipment.

Private Picture Copyright: WWW.MBSM.PRO

MBSM.pro, Compressor, 13HP, Danfoss, Performer, Scroll Compressor, Sm160, Sm161t4vc, Refrigeration Chiller, 3 ph, 380 v, 38BB 055 – 240, 38bb-250 9e/k, 38BB 250, 250 = 250000 kBTu/hr, 30 Ton, r22, 19 Kg, suction 1-1/8"–2, refoulement 5/8"–2