

Mbsm.pro, Compressor, QD series, Compressor, Refrigerator, R134, R12, R134A, R406, R12/R134A/R406-LBP compressor performance parameter

Category: Archivation, compressor
written by www.mbsm.pro | 12 April 2022




Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Compressor, QD series, Compressor, Refrigerator, R134, R12, R134A, R406, R12/R134A/R406-LBP compressor performance parameter

Compressor, QD110, 3/10 HP, LBP, R12/R406, 276w, R12, R406

Category: compressor
written by www.mbsm.pro | 12 April 2022



Private Picture Copyright: WWW.MBSM.PRO

Quantité(Pièce) 1 – 30 31 – 70 71 – 150 >150
 Durée estimée (jours) 5 10 15 À négocier
 Tension: 220 V-240 V
 50 HZ
 Compresseur LBP R12/R406

Modèle	Valage (V)	Fréquence (Hz)	Déplacement (CC)	Capacité (W)	Puissance d'entrée (W)	Type de moteur	De charge d'huile (CC)	Type de refroidissement	Poids (Kg)
QD30	220-240	50	3.0	62	81	RSIR	180	ST	6.3
QD36	220-240	50	3.6	75	93	RSIR	180	ST	6.4
QD55	220-240	50	5.5	133	110	RSIR	240	ST	8.4
QD65	220-240	50	6.5	155	130	RSIR	240	ST	8.4
QD75	220-240	50	7.5	176	146	RSIR	240	ST	8.6
QD85	220-240	50	8.5	202	168	RSIR	240	ST	8.9
QD110	220-240	50	11.0	276	236	RSIR	240	ST	9.9
QD125	220-240	50	12.5	305	254	RSCR	280	ST	11.2



Private Picture Copyright: WWW.MBSM.PRO

R406a 220~240V/50Hz

LBP
低背压

序号 No.	应用类型 Application	产品系列 Serial	产品型号 type	马力 Hp	电压/频率 Power Supply (V/Hz)	电机类型 Motor type	制冷量 Capacity		COP Power Efficiency		启动器 Starting Device	启动电容 Starting Capacitor (μF)	运行电容 Running Capacitor (μF)	冷却方式 Cool
							ASHRAE (-23.3°C)	CECOMAF (-25°C)	ASHRAE (-23.3°C)	CECOMAF (-25°C)				
							w		COP (w/w)					
1	LBP 低背压	WT	QD55	1/6	220~240V ~50Hz	RSIR	130	98	1.04	0.81	PTC	/	/	S
2			QD65	1/5		RSIR	158	119	1.08	0.84		/	/	S
3			QD75	1/4		RSIR	176	132	1.09	0.85		/	/	S
4			QD85	1/4		RSIR	202	152	1.10	0.86		/	/	S
5			QD91	1/4		RSIR	216	162	1.12	0.87		/	/	S
6	LBP 低背压	WQ	QD110	3/10	220~240V ~50Hz	RSIR	271	203	1.17	0.91	重锤 Starting Relay	/	/	F
7			QD128	1/3		RSIR	306	230	1.18	0.92		/	/	F
8			QD142	2/5		CSIR	333	250	1.19	0.93		80	/	F
9	LBP 低背压	SC	QD168	1/2	220~240V ~50Hz	CSIR	380	330	1.15	1.06	电流式 Current	80	/	F2
10			QD180	1/2		CSIR	440	382	1.15	1.07		80	/	F2
11			QD210	3/5		CSIR	510	443	1.17	1.08		80	/	F2

