

Mbsm.pro, Compressor , s36G, 1/10 hp, 1ph 220v/50hz, R134a, 32g, water-cooler, BLY-F/950

Category: compressor

written by www.mbsm.pro | 2 February 2025



Private Picture Copyright : WWW.MBSM.PRO

Information	Value
Model	BLY-F (905)
Rated Voltage	220-240V~
Rated Frequency	50/60Hz
Heating Power	450W
Total Power	550W
Maximum Rated Wattage of Lamps	0.5W
Cooling Capacity	1.5L/h
Cooling Consumption	0.100Kwh/H
Rated Cooling Current	0.8A
Refrigerant	R134a/32g
Climate Class	T
Protection Class	I
Foam	EPS
Waterproof Degree	IPX0
Made in	China

Water Dispenser / Mini Fridge Compressor (1/10HP)

Refrigeration Compressor Type Reciprocating Compressor

Refrigerant R134A

Usage Water Dispenser / Small Fridge / Minibar / etc

Warranty	N/A
Voltage	220-240V / 50Hz
Displacement	3.6 cm ³
Model No.	S36G / QD36
Cooling Power (W)	80W
Cooling Power (HP)	1/10 HP

Small refrigeration compressor mainly used in:

- Water Dispenser (cooling cabinet models)
- Small Refrigerator / Mini Bar / Ice Machines
- Other small refrigerating equipment

Cooling Power: 85W (1/10 HP)

Electricity required: 220-240V / 50Hz

1. Compressor (Model S36G)

- **Purpose:** The core component for pressurizing refrigerant in a cooling cycle.
 - **Model S36G:** Likely a specific compressor model (possibly from a brand like Secop, Danfoss, or a regional manufacturer). Verify with manufacturer documentation for exact specs.
 - **Application:** Small-scale systems (e.g., commercial water coolers, medical devices, or compact refrigeration) due to the small refrigerant charge.
-

2. Refrigerant (R134a, 32g)

- **R134a:** A common hydrofluorocarbon (HFC) refrigerant used in medium-temperature systems (e.g., refrigerators, AC units, water coolers).
 - **32g Charge:** Indicates a small system, typical for portable or compact units. Ensure the charge matches manufacturer specifications to avoid inefficiency or damage.
-

3. Water-Cooler System

- **Water-Cooled Condenser:** Uses water (instead of air) to dissipate heat, improving efficiency. Requires a water supply, pump, and possibly a cooling tower.
 - **Applications:** Often found in commercial settings (e.g., water dispensers, industrial chillers, or high-efficiency HVAC systems).
-

4. BLY-F/950

- Likely a **component model**, such as:
 - **Filter drier:** Removes moisture/contaminants from refrigerant.
 - **Pressure switch:** Safety device to control system pressure.
 - **Control board/Valve:** Part of the system's electrical or flow regulation.
 - Check manufacturer manuals or suppliers for exact function.
-

Key Considerations

1. **Compatibility:** Ensure the compressor (S36G) is designed for R134a and water-cooled operation.
 2. **Refrigerant Charge:** Confirm 32g is correct (undercharging/overcharging affects performance).
 3. **Water Cooling:** Check for scale buildup, water flow rate, and pump functionality.
 4. **BLY-F/950 Replacement:** Cross-reference with OEM parts or contact the system manufacturer.
-

Troubleshooting Tips


- **Low Cooling Efficiency:** Check refrigerant charge, water flow, or condenser cleanliness.
- **Component Failure:** Test the BLY-F/950 part (e.g., continuity for switches, clogging in filter driers).
- **Noise/Leaks:** Inspect the compressor and refrigerant lines.

Products Introduction:

Voltage / frequency(V/Hz)	Horsepower (hp)	Model	Displacement (cc/rev)	Motor type	Cooling capacity+/-5% ASHRAE(-23.3°C)			Input Power +/-5% w	COP+/-7% ASHRAE(-23.3°C)			Cooling
					(kcal/h)	(W)	(Btu/h)		(kcal/h)	(W)	(Btu/h)	
					220-240V~ 50/60Hz							
	1/14hp	ASV20H	2.0cc	RSIR	41	48	164.00	56.00	0.73	0.85	2.9	ST
	1/13hp	ASV25H	2.5cc	RSIR	50	58	198.00	68.00	0.73	0.85	2.9	ST
	1/12hp	ASV30H	3.0cc	RSIR	60	70	239.00	82.00	0.73	0.85	2.9	ST
	1/12hp	S30G	3.0cc	RSIR	56	65	222.00	72.00	0.77	0.9	3.07	ST
	1/10hp	S36G	3.6cc	RSIR	69	80	273.00	89.00	0.77	0.9	3.07	ST
	1/8hp	ASW43H	4.3cc	RSIR	106	123	420.00	98.00	1.08	1.25	4.27	ST
	1/6hp	ASW53H	5.3cc	RSIR	120	140	478.00	112.00	1.08	1.25	4.27	ST
	1/5hp	ASW65H	6.5cc	RSIR	143	165	566.00	132.00	1.08	1.25	4.27	ST
	1/4hp	ASW75H	7.5cc	RSIR	168	190	665.00	152.00	1.08	1.25	4.27	ST
	1/4+hp	ASQ91H	9.1cc	RSIR	189	220	751.00	176.00	1.08	1.25	4.27	ST
	1/3hp	ASQ110H	11.0cc	RSIR	241	280	955.00	215.00	1.11	1.3	4.43	ST
	1/3+hp	ASQ128H	12.8cc	RSIR	280	326	1112.00	251.00	1.11	1.3	4.43	ST
115-127V/60Hz												
	1/14hp	ASV20HD	2.0cc	RSIR	47	55	188.00	65.00	0.73	0.85	2.9	ST
	1/10hp	ASV25HD	2.5cc	RSIR	56	65	222.00	78.00	0.77	0.9	3.07	ST
	1/12hp	ASV30HD	3.0cc	RSIR	69	80	273.00	100.00	0.77	0.9	3.07	ST
	1/8hp	ASW43HD	4.3cc	RSIR	116	135	460.00	108.00	1.08	1.25	4.27	ST
	1/6hp	ASW53HD	5.3cc	RSIR	138	160	546.00	128.00	1.08	1.25	4.27	ST
	1/5hp	ASW65HD	6.5cc	RSIR	167	194	662.00	147.00	1.14	1.32	4.5	ST
	1/4hp	ASW75HD	7.5cc	RSIR	196	228	777.00	173.00	1.14	1.32	4.5	ST
FC:Fancooling	RSIR:ResistanceStartInductionRun						EvaporatingTemp.: -23.3°C(-10°F)		1watt=3.41Btu/Hr			
OC:Oilcooling	RSCR:ResistanceStartCapacitorRun						CondensingTemp.: 54.4°C(130°F)		1watt=0.86Kcal/Hr			
ST:Static	CSIR:CapacitorStartInductionRun						GasSuperheatedto: 32.2°C(90°F)		1Kcal/Hr=3.97Btu/Hr			
	CSR:CapacitorStartCapacitorRun						Liquidsub-cooledto: 32.2°C(90°F)					
							AmbientTemp.: 32.2°C(90°F)					

As a result of a serial policy of constant development, technical specifications may be subject to change.





Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO

- File uploaded successfully: [Open file in a new window](#)

File Information:

File Name: Mbsm-tn-media-_Compressor-s36G-R134a-32g-water-cooler-BLY-F-950.jpg

File Type: image/jpeg

File Size: 436.6 KB

File Extension: jpg

- File uploaded successfully: [Open file in a new window](#)

File Information:

File Name: Mbsm-tn-media-Compressor-s36G-R134a-32g-water-cooler-BLY-F-950.jpg

File Type: image/jpeg

File Size: 435.14 KB

File Extension: jpg

File uploaded successfully: [Open file in a new window](#)

File Information:

File Name: Mbsm-tn-media-Compressor-s36G-R134a-32g-water-cooler-BLY-F-950.jpg

File Type: image/jpeg

File Size: 549.08 KB

File Extension: jpg

File uploaded successfully: [Open file in a new window](#)

File Information:

File Name: Mbsm-tn-media-Compressor-s36G-R134a-32g-water-cooler-BLY-F-950.pdf

File Type: application/pdf

File Size: 296.7 KB

File Extension: pdf