

Sangchai refrigeration, FL series, RL series, CL series, Hitachi Compressor, FL1675-sc, 1/5 Hp, R-134A, Low back pressure, 160 w, Displacement 7.5 cm cube, 220-240 v 50 hz

Category: compressor

written by www.mbsm.pro | 5 January 2021

Sangchai refrigeration, FL series, RL series, CL series, Hitachi Compressor, FL1675-sc, 1/5 Hp, R-134A, Low back pressure, 160 w, Displacement 7.5, 220-240 v 50 hz

Hitachi Hermetic Compressors

FL Series

STANDARD MODEL

Application & Refrigerant LBP R134a

Model	Nominal Power		F	Cooling Capacity			D	Cooling			O	Wg	Motor Type	Power Source					Dimension				
	HP	W		Hz	W	Kcal/h		BTU/h	cm3	N				Oil	Fan	cm3	Kg	1		2	3	4	5
																		H		P	R	S	T
FL0634	1/12	65	50	78	67	266	3.42	•			200	6.8	RSIR RSCR CSIR	•			•		Type1-165				
			60	90	77	307											•	•	•				
FL0739	1/10	75	50	95	82	324	3.94								7.8		•			•		Type1-179 Type2-180	
			60	108	93	368											•	•	•				
FL0845	1/8	85	50	105	90	358	4.50									270	8.1	•	•		•		
			60	118	101	403											•	•	•				
FL1052	1/6	100	50	120	103	409	5.19								8.3		•			•		Type1-195 Type2-200	
			60	140	120	478										•	•	•					
FL1157		110	50	135	116	461	5.70								240	8.7	•			•			
			60	158	136	539											•	•	•				
FL1262	1/5	125	50	150	129	512	6.23				•				320	9.5		•			•		
			60	170	146	580											•	•	•				
FL1675		160	50	185	159	631	7.47		•	•	300	10.6		•			•						
			60	210	181	717							•	•	•								
FL1888	1/4	180	50	215	185	734	8.83		•	•	300	11.1		•			•						
			60	250	215	853							•	•	•								

Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO

Detail of Label

Series name/Refrigerant

F	=R134a
R	=R404A
C	=R600a

Application category

L = Low back pressure
H = High back pressure

Nominal power (Out put)

Sign	Output(W)	Sign	Output(W)
04	45	15	150
05	55	16	160
06	65	17	170
07	75	18	180
08	85	20	200
10	100	25	250
11	110	35	350
12	125	40	400
14	140	45	450

Nominal voltages / Power source

Sign	Phase/voltage/frequency	Sign	Phase/voltage/frequency
H	1Ø 100 V 50/60 Hz	S	1Ø 220 ~ 240 V 50 Hz
P	1Ø 110 V 120 V 60 Hz	D	1Ø 100 V 50/60 Hz
U	1Ø 127 V 60 Hz	T	3Ø 200 V 50/60 Hz
R	1Ø 200 ~ 220 V 60 Hz		

Displacement

Sign	Displacement(Cm ³)	Sign	Displacement(Cm ³)
24	2.4	62	6.2
26	2.6	66	6.6
34	3.4	75	7.5
39	3.9	86	8.6
45	4.5	97	9.7
52	5.2	11	11.0
57	5.7		

Development

A = With oil charge
T = With out oil charge

www.mbsm.pro

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_Hitachi-catalogueTélécharger

Mbsm_dot_pro_private_PDF_FL1675Télécharger