

# MBSM.PRO , HYE69YL , Compressor (LBP) , China R134a ,Huayi Compressor Co. , Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

written by Jamila | 6 October 2018

MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi  
Compressor Co. , Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

| Test conditions                   | According to ASHRAE      |
|-----------------------------------|--------------------------|
| Evaporating temperature           | -23.3[°C]                |
| Condensing temperature            | 54.4[°C]                 |
| Subcooling temperature            | 32.2[°C]                 |
| Suction temperature               | 32.2[°C]                 |
| Ambient temperature               | 32.2[°C]                 |
| Working condition limit:R134a     |                          |
| Max ambient temperature           | 43[°C]                   |
| Evaporation temperature range     | -35~-15[°C]              |
| Working voltage range.            | 187~254/98~127[V]        |
| Max discharge pressure            | 2.0[Mpa](gauge pressure) |
| Max allowable housing temperature | 95[°C]                   |
| Max discharge temperature         | 125[°C]                  |
| Max pressure housing endured      | 2.7[Mpa](gauge pressure) |

Low voltage start

0.4/0.4Mpa(gauge  
pressure)187V/98V

Product model:HYE69YL

Cooling capacity:195W

COP[W/W]:1.15

Voltage[V]:220-240~

Frequency(Hz):50



## Products

### R134a Compressor (LBP)

HYE Serie  
HY Serie  
HYB Serie  
HYS Serie

### R600a Compressor (LBP)

HYE Serie  
HY Serie  
HYB Serie  
HYS Serie

### R134a Compressor (MBP,HBP)

HY Serie  
HYS Serie

Newest Catalog Download

Product model:HYE69YL  
Cooling capacity:195W  
COP (W/W) :1.15  
Voltage (V) :220-240~  
Frequency(Hz):50

| Test conditions                      | According to ASHRAE                |
|--------------------------------------|------------------------------------|
| Evaporating temperature              | -23.3°C                            |
| Condensing temperature               | 54.4°C                             |
| Subcooling temperature               | 32.2°C                             |
| Suction temperature                  | 32.2°C                             |
| Ambient temperature                  | 32.2°C                             |
| <b>Working condition limit:R134a</b> |                                    |
| Max ambient temperature              | 43[°C]                             |
| Evaporation temperature range        | -35~-15[°C]                        |
| Working voltage range.               | 187~254/98~127[V]                  |
| Max discharge pressure               | 2.0[Mpa](gauge pressure)           |
| Max allowable housing temperature    | 95[°C]                             |
| Max discharge temperature            | 125[°C]                            |
| Max pressure housing endured         | 2.7[Mpa](gauge pressure)           |
| Low voltage start                    | 0.4/0.4Mpa(gauge pressure)187V/98V |

PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)



**HY 81 Y**

**1 / 4 HP**



**HYE 55 YL 63**

**1 / 6 HP**



**HYE 60 YL 63**

**1 / 5 HP**



**HYE 69 YL**

**1 / 4 HP**



**HYE 125 MSU**

**1 / 4 HP**

