

Capacity (EN 12900/CECOMAF)

watt

Comp.\°C	-35	-30	-25	-23.3	-20	-15	-10
TLS5FT	47.8	70.7	98.0	109	131	170	216

Capacity (ASHRAE)

watt

Comp.\°C	-35	-30	-25	-23.3	-20	-15	-10
TLS5FT	58.9	87.2	121	134	161	209	267

Power consumption

watt

Comp.\°C	-35	-30	-25	-23.3	-20	-15	-10
TLS5FT	84.5	99.2	114	120	131	147	165

Current consumption

A

Comp.\°C	-35	-30	-25	-23.3	-20	-15	-10
TLS5FT	0.96	0.98	1.01	1.02	1.05	1.10	1.15

COP (EN 12900/CECOMAF)

W/W

Comp.\°C	-35	-30	-25	-23.3	-20	-15	-10
TLS5FT	0.57	0.71	0.86	0.91	1.00	1.15	1.30

COP (ASHRAE)

W/W

Comp.\°C	-35	-30	-25	-23.3	-20	-15	-10
TLS5FT	0.70	0.88	1.06	1.12	1.24	1.42	1.61

Test conditions

Condensing temperature
Ambient and suction gas temp.
Liquid temperature
Static cooling, 220V 50Hz,
PTC consumption incl.

EN 12900/CECOMAF

55°C
32°C
55°C

ASHRAE

55°C
32°C
32°C

Accessories

Devices	Fig.	TLS5FT
PTC starting device 6.3 mm spades 4.8 mm spades	a1	103N0011 103N0018
Starting relay	a2	117U6000
Cover	b	103N2010
Starting capacitor 60 µF	c	117U5014
Cord relief	d	103N1010
Protection screen for PTC	g	103N0476
Mounting accessories		
Bolt joint for one compressor		118-1917
Bolt joint in quantities		118-1918
Snap-on in quantities		118-1919

