

Compressor Technical Data

Model **GL75AA** Code **422090345116****LBP**

General Data

Refrigerant: R134a
 Application: LBP
 Evaporating Temperature Range: -30°C to -10°C
 Voltage/Frequency: 220-240V 50Hz 1~
 Compressor Cooling: Static
 Expansion Device: Capillary Tube
 Packaging Quantity: Multi - 96:120 pcs
 Approvals: CE-VDE-GOST



Mechanical Data

Oil Charge: 345 cm3
 Oil Type Configuration: ester
 Oil Type Viscosity: 19 cSt
 Weight: 9.9 Kg

Electrical Data

Motor Type: RSIR / RSCR*
 Voltage working range at 50 Hz: 187-264V
 Maximum Motor Temperature: 130°C
 Locked Rotor Current: 11.5 / 5.6 A
 Start Winding Resistance: 22.00 Ω at 25°C
 Run Winding Resistance: 11.60 Ω at 25°C
 Phase : 1 ph


External Characteristics

Internal Diameter (mm)
 Suction Connector 6.5
 Discharge Connector 4.9
 Process Connector 6.5
 Material Copper


Electrical Components

Component Type
 Starting Device: PTC 14 Ω
 Motor Protection: T0502/xx


Circuit Diagram for Mod.90 Terminal Board



Circuit Diagram for U.H. Terminal Board




Recommended Transport
Positions when fitted into
appliances







MCMC compressors reserves the right to change the data without prior notice

10th of Ramadan City - (Cairo) Egypt
 Industrial Zone A-2
 P.o Box : 1001 (10th of Ramadan)
 Tel. : 0554 - 413322 (10 lines)
 Fax. : 0554 - 413161 - 413029
 Web site : <http://www.zmcegypt.com>



العاشر من رمضان
 المنطقة الصناعية أ - ٢
 ص.ب : ١٠٠١ العاشر من رمضان
 تليفون : ٤١٣٣٢٢ - ٠٥٥٤ (١٠ خطوط)
 فاكس : ٤١٣١٦١ - ٤١٣٠٢٩ (٠٥٥٤)

PERFORMANCE CURVE DATA :



Test Condition: Ashrae, Static, Return Gas 32°C Subcooling OK, Evaporating: 23.3°C, Condensing: 55°C, Ambient: 32°C


10th of Ramadan City - (Cairo) Egypt
Industrial Zone A-2
P.o Box : 1001 (10th of Ramadan)
Tel. : 0554 - 413322 (10 lines)
Fax. : 0554 - 413161 - 413029
Web site : <http://www.zmcegypt.com>



العاشر من رمضان
المنطقة الصناعية أ - ٢
ص.ب : ١٠٠١ العاشر من رمضان
تليفون : ٤١٣٣٢٢ - ٠٥٥٤ (١٠ خطوط)
فاكس : ٤١٣١٦١ - ٤١٣٠٢٩ (٠٥٥٤)

GM, GN and GL models

HL and HP models




Standard dimensions for mounting hole centres: 170x70 mm

Special feet

Models	Distance between holes	Holes diameter
GM/GN/HL/HP/GP	165 x 101.6	4 x 19
	170 x 70	6 x 165

Tube internal diameter "GM", "GN", "GL", "HL"	"HP" and "GP"		
Material	Suction	Service	Discharge
Copper steel / copper	6.1	6.1	4.9
Copper	6.1	6.1	5.1
Copper	6.5	6.5	4.9
Copper	8.1	8.1	6.5

Mounting accessories



10th of Ramadan City - (Cairo) Egypt
Industrial Zone A-2

P.o Box : 1001 (10th of Ramadan)

Tel. : 0554 - 413322 (10 lines)

Fax. : 0554 - 413161 - 413029

Web site : <http://www.zmcegypt.com>



العاشر من رمضان


المنطقة الصناعية أ - ٢

ص.ب: ١٠٠١ العاشر من رمضان

تليفون : ٤١٣٣٢٢ - ٠٥٥٤ (١٠ خطوط)

فاكس : ٤١٣١٦١ - ٤١٣٠٢٩ (٠٥٥٤)

Terminal board 'A' for GL, GM, GN, HL and HP models



Terminal board 'B' for GL, GM, GN, HL and HP models

