

# Catalogue

### Product Select

Product Type: **Compressors** ▼

Search Compressor:

Application: **Any** ▼

Refrigerant: **Any** ▼

Voltage: **Any** ▼

Frequency: **Any** ▼

Compressor Cooling: **Any** ▼

Green Cooling:

### Unit settings

kCal/h, W | °C | Kg | cm

BTU/h | °F | lbs | in

### General Catalogue

PDF File

[Download](#)

### Working conditions


Standard

Particular

### Standard Conditions

	CECOMAF		ASHRAE		HCB CECOMAF		HCB ASHRAE	
	LBP	HMBP	LBP	HMBP	MBP	VHBP	MBP	VHBP
Evaporating temp. (°C)	-25	5	-23.3	7.2	-10	25	-10	25
Condensing temp. (°C)	55	55	55	55	55	70	55	70
Liquid temp. (°C)	55	55	32	46	55	70	46	61
Suction temp. (°C)	32	32	32	35	32	32	35	35
Ambient temp. (°C)	32	32	32	35	32	32	35	35

694 compressors found: page 1 / 35

									ASHRAE (*)		CECOMAF (*)		
Model	Displacement (cm³)	Refrigerant	Application	Compressor Cooling	Voltage/Frequency	Frequency (Hz)	Motor Type	Cooling (kCal/h)	COP (W/W)	Cooling (W)	COP (W/W)	Technical Data Sheet (*)	
<b>B22G</b>	2,20	R134a	HBP	S/F	220-240V 50Hz ~1	50	RSIR	160	1,94	152	1,64	<b>B22G</b>	
<b>B22G5</b>	2,20	R134a	HBP	S/F	110-115V 60Hz ~1	60	RSIR	194	2,13	188	1,83	<b>B22G5</b>	
<b>B25G</b>	2,60	R134a	HBP	S/F	220-240V 50/60Hz ~1	60	RSIR	232	2,10	224	1,80	<b>B25G</b>	
<b>B25G</b>	2,60	R134a	HBP	S/F	220-240V 50/60Hz ~1	50	RSIR	208	2,08	202	1,78	<b>B25G</b>	
<b>B25G5L</b>	2,60	R134a	HBP	S/F	115V 60Hz ~1	60	CSIR	240	2,29	231	1,94	<b>B25G5L</b>	
<b>B25GL</b>	2,60	R134a	HBP	S	220-240V 50Hz ~1	50	CSIR	196	2,16	186	1,81	<b>B25GL</b>	
<b>B30G</b>	3,10	R134a	HBP	S/F	220-240V 50Hz ~1	50	RSIR	234	2,06	229	1,77	<b>B30G</b>	
<b>B30G</b>	3,10	R134a	HBP	S/F	220-240V 50Hz ~1	50	CSIR	234	2,06	229	1,77	<b>B30G</b>	
<b>B30G5</b>	3,10	R134a	HBP	S/F	110-115V 60Hz ~1	60	RSIR	270	2,08	262	1,79	<b>B30G5</b>	
<b>B35G5</b>	3,50	R134a	HBP	S/F	110-115V 60Hz ~1	60	CSIR	315	2,12	304	1,80	<b>B35G5</b>	
<b>B35GL</b>	3,50	R134a	HBP	S/F	220-240V 50Hz ~1	50	CSIR	272	2,34	262	2,00	<b>B35GL</b>	
<b>B38G</b>	3,80	R134a	HBP	S/F	220-240V 50Hz ~1	50	CSIR	298	2,23	291	1,91	<b>B38G</b>	
<b>B38G</b>	3,80	R134a	HBP	S/F	220-240V 50/60Hz ~1	60	CSIR	349	2,31	339	1,98	<b>B38G</b>	
<b>B38G</b>	3,80	R134a	HBP	S/F	220-240V 50/60Hz ~1	50	CSIR	301	2,22	288	1,87	<b>B38G</b>	
<b>B38G5L</b>	3,80	R134a	HBP	S/F	110-115V 60Hz ~1	60	CSIR	363	2,13	353	1,83	<b>B38G5L</b>	
<b>B43GL</b>	4,30	R134a	HBP	F	220-240V 50Hz ~1	50	RSIR	360	2,06	348	1,75	<b>B43GL</b>	
<b>GE70TG</b>	6,70	R134a	HBP	F	220-240/230V 50/60Hz ~1	50	CSIR	604	2,36	584	2,01	<b>GE70TG</b>	
<b>GE70TG</b>	6,70	R134a	HBP	F	220-240/230V 50/60Hz ~1	60	CSIR	721	2,44	701	2,11	<b>GE70TG</b>	
<b>GE80TG</b>	8,10	R134a	HBP	F	220-240/230V 50/60Hz ~1	50	CSIR	714	2,20	687	1,89	<b>GE80TG</b>	
<b>GE80TG</b>	8,10	R134a	HBP	F	220-240/230V 50/60Hz ~1	60	CSIR	834	2,28	798	1,95	<b>GE80TG</b>	

(\*) Under standard conditions

(\*\*) Version 3

---

## Navigate

About Us  
Products  
[Catalogue](#)  
Technical Information  
News  
Distribution Network  
Customer Area  
Contact

Legal notice  
Cookies  
Site Map

## Social

- [LinkedIn](#)
- [Our Blog](#)

## Get in Touch

**Mail Us**  
[info@huayicompressor.es](mailto:info@huayicompressor.es)

**Call**  
+34 93 710 60 08

**Address**  
Antoni Forrellad, 2 - 08192  
Sant Quirze del Vallés  
Barcelona - Spain

### The Group

The logo for Changhong, featuring the word "CHANGHONG" in red capital letters followed by the Chinese characters "长虹" in red.The logo for Huayi, featuring a green stylized mountain icon above the Chinese characters "华意压缩" in green, with the word "HUAYI" in small black capital letters below the icon.