

Performance

Application : Low Back Pressure

Refrigerant : R134a (CF₃CH₂F)

Evaporator Temperature Range : -35°C to -5°C

Series	Model	Displacement (cm ³)	Voltage / Frequency	Motor Type	ASHRAE		CECOMAF	
					Capacity	COP	Capacity	COP
					W	W/W	W	W/W
	SB24C45GAU6	2.4	115V 60Hz	RSIR	50	0.85	-	-
				RSCR	-	-	-	-
	SB24C50GA00	2.4	100V 50/60Hz	RSIR	37 / 45	0.60 / 0.70	-	-
				RSCR	-	-	-	-
	SB24C50GAU6	2.4	115V 60Hz	RSIR	45	0.80	-	-
				RSCR	-	-	-	-
	SB24C50GAW5	2.4	220/240V 50Hz	RSIR	37 / 37	0.71 / 0.64	-	-
				RSCR	-	-	-	-
	SB30C50GAU6	3.0	115V 60Hz	RSIR	72	0.93	-	-
				RSCR	-	-	-	-
	SB30C50GAW5	3.0	220/240V 50Hz	RSIR	60 / 60	0.81 / 0.74	-	-
				RSCR	-	-	-	-
	SB30C55GAT6	3.0	110V 60Hz	RSIR	72	0.83	-	-
				RSCR	-	-	-	-