

AC Tropical R22 (50Hz)

1Φ, 220-240V

SPECIFICATION

1Φ, 220-240V

Model	Displacement	Cooling Capacity		EFF	COP	Input	Oil Charge	Net Weight	Test Condition	Dimension
	CC/Rev	BTU/H	W	BTU/Wh	W/W	W	cc	kg		
UR4B092JT	16.1	9,300	2,726	10.0	2.93	930	340	11.8	ASHRAE HBP	44-2
UR4D124JH	21.0	12,400	3,634	9.7	2.84	1,278	380	12.7	ASHRAE HBP	44-7
UR4D129JT	21.7	12,800	3,751	9.6	2.81	1,333	380	12.7	ASHRAE HBP	44-16
UR8B180JH	30.4	18,400	5,393	9.4	2.76	1,957	550	16.4	ASHRAE HBP	48-10
UR8B200JT	32.5	19,500	5,715	9.3	2.73	2,097	550	16.5	ASHRAE HBP	48-11
UR8D165JH	27.8	16,500	4,836	10.2	2.99	1,618	550	16.5	ASHRAE HBP	48-12
UR5A250JH	41.8	25,300	7,415	10.1	2.97	2,500	550/800	22.3/22.6	ASHRAE HBP	55-5

