BS	

型号 Kodel 되力 Power)) ent	42 30	类型 Type	制冷量 Cooling Capacity										COP		Reft -
	έЪ	。 御 記	UISPIAcement 冷却方式 Cooling											CECOMAF	ASHRAE	CECOMAF	电 3
		气缸 Displa		电机类型 Motor Typ	-35	-30	-25	-23. 3	-20	-15	-10	-5	0	-25	-23. 3	-25	运行电容 Bun formit
	HP	cm3			w	w	w	w	W	w	W	w	w	w	w/w	w/w	μF
220~2400 A系列AS		000a(#		, Alumi	nium v	ire mo	cor)										
	1/8	5.8	S	RSCR	52	67	87	93	119	148	183			70.7	1.42	1.11	3
A100CY1	1/8	5.8	S	RSIR	52	67	87	93	119	148	183			71	1.35	1.07	-
D系列 D S		0.0	0			0.	0.										
D40CY1	1/14	4	S	RSIR	28	34	43	50	55	70	90			38	1.00	0.75	
D53CY1	1/10	5.3	S	RSIR	41	49	65	75	90	115	142			57	1.16	0.90	
D53CY1A	1/10	5.3	S	RSIR	41	49	65	75	90	115	142			57	1.25	0.99	
S系列 S S			-														
S53CY1	1/10	5.3	S	RSIR	41	49	65	75	90	115	142			57	1.28	1.0	
S65CY1	1/8	6.5 6.5	S S	RSIR	52 52	67 67	87 87	95 95	119 119	148 148	183			72	1.41 1.46	1.10	
S65CY1A S65CY1B	1/8	6.5	S	RS IR RS IR	52	67	87	95	119	148	183 183			72	1.40	1.14	
S75CY1	1/7	7.5	S	RSIR	65	79	104	120	134	171	216			91	1.30	1.03	
S80CY1	1/6	8	S	RSIR	87	102	125	137	164	208	270			106	1.30	1.03	
SK53CY1	1/13	5.6	S	RSCR	41	49	65	75	90	115	142			57	1.45	1.13	4
SK65CY1A	1/8	6.5	S	RSCR	52	67	87	95	119	148	183			72	1.55	1.21	4
SK75CY1	1/7	7.5	S	RSCR	65	79	104	120	134	171	216			91	1.53	1.20	4
SK80CY1	1/6	8	S	RSCR	87	102	125	137	164	208	270			106	1.50	1.17	4
SU60CY1	1/8	6	S	RSCR	52	67	87	95	119	148	183			72	1.63	1.27	3
SU75CY1	1/7	7.5	S	RSCR	65	79	104	120	134	171	216			91	1.63	1.27	3
SU80CY1	1/6	8	S	RSCR	87	102	125	137	164	208	270			104	1.60	1.25	4
SZ60CY1	1/8	6	S	RSCR	52	67	87	95	119	148	183			72	1.73	1.35	3
SZ75CY1	1/7	7.5	S	RSCR	65	79	104	120	134	171	216			91	1.72	1.34	3
SJ60CY1	1/8	6	S	RSCR	52	67	87	95	119	148	183			72	1.80	1.40	2.5
L 系列 L S L88CY1	1/5	8.8	S	RSIR	98	115	143	155	190	238	308			118	1.36	1.1	
L88CY1A	1/5	8.8	S	RSIR	98	115	143	155	190	238	302			119	1.15	0.87	
LU88CY1	1/5	8.8	S	RSCR	98	115	143	155	190	238	308			118	1.63	1.27	5
L100CY1	1/4-	10	S	RSIR	108	126	162	170	207	252	311			136	1.40	1.10	
LK100CY1	1/4-	10	S	RSCR	108	126	162	170	207	252	311			136	1.53	1.20	4
LU100CY1	1/4-	10	S	RSCR	108	126	162	170	207	252	311			136	1.60	1.25	4
LZ100CY1	1/4-	10	S	RSCR	108	126	162	170	200	252	311			136	1.70	1.33	4
220~240	/ 50Hz R	134a(铅	3线电机	. Alumi	nium v	vire mo	otor)										
E系列 E S																	
E1130CZ1	3/8+	12.1	F1	CSR	116	187	284	325	400	550	736			247	1.26	0.95	
E1134CZ1	1/2	13.5	F1	CSIR	131	217	318	375	445	591	774			285	1.26	0.95	
<u>115V 60Hz</u> D系列 D S		<u> </u>	HL AIU	IINIUM	wiren	otor)											
	1/10	2.5	S	RSIR	32	44	57	67	80	100	135	168	214	51	0.95	0.72	
D25BZ1A	1/10	2.5	S	RSIR	32	44	57	67	80	100	135	168	214		1.10		
DK25BZ1	1/10	2.5	S	RSCR	34	46	59	68	82	102	136	170	215	-	1.30		12
D21BZ1	1/13	2.1	S	RSIR	22	30	45	55	66	86	100	130	160	40	1.0	0.79	
DK21BZ1	1/14	2.1	S	RSCR	22	30	45	55	66	86	100	130	160	40	1.30	0.99	12
220~240									00	100	105	100	0.1.1		0.05	0.70	
D25DZ1	1/10					44	57	67	80	100	135	168	214	51	0.95	0.72	
115~127V 60Hz R134a(铝线电机 Aluminium wire motor) L系列 L Series																	
LU66XZ1	1/4	6.6	S	RSCR	88	130	192	210	257	323	398			160	1.56	1.18	12

测试工况 Test Condition