

型号 Model	马力 Power	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量Cooling Capacity								COP(with PTC)		运行电容Run Capacitor
					ASHRAE							CECOMAF	ASHRAE	CECOMAF	
					-35	-30	-25	-23.3	-20	-15	-10	-25	-23.3	-25	
	HP	cm <sup>3</sup>			w	w	w	w	w	w	w	w	w/w	w/w	μF

LBP

220V-240V 50HZ R600a

D系列 D Series

D40CY	1/14	4.0	S	RSIR	28	34	43	50	55	70	90	38	1.06	0.83	
D43CY	1/11	4.3	S	RSIR	36	47	60	65	79	105	136	49	1.20	0.94	
D53CY	1/10	5.3	S	RSIR	41	49	65	75	90	115	142	57	1.16	0.90	
D65CY	1/8	6.5	S	RSCR	52	67	87	95	119	148	183	72	1.33	1.03	
DG53CY	1/10	5.3	S	RSCR	41	49	65	75	90	115	142	57	1.35	1.05	3
DU40CY	1/14	4.0	S	RSCR	29	36	46	55	62	79	102	42	1.48	1.15	2
DU53CY	1/10	5.3	S	RSCR	41	49	65	75	90	115	142	57	1.50	1.17	3

S系列 S Series

S65CY	1/8	6.5	S	RSIR	52	67	87	95	119	148	183	72	1.45	1.13	
S65CYA	1/8	6.5	S	RSIR	52	67	87	95	119	148	183	72	1.5	1.17	
S75CY	1/7	7.5	S	RSIR	65	79	104	120	134	171	216	91	1.35	1.05	
SK53CY	1/10	5.3	S	RSCR	41	49	65	75	90	115	142	57	1.51	1.18	4
SK65CY	1/8	6.5	S	RSCR	52	67	87	95	119	148	183	72	1.55	1.21	4
SK65CYA	1/8	6.5	S	RSCR	52	67	87	95	119	148	183	72	1.60	1.25	4
SU60CY	1/8	6.0	S	RSCR	52	67	87	95	119	148	183	72	1.65	1.29	3
SU75CY	1/7	7.5	S	RSCR	65	79	104	120	134	171	216	91	1.65	1.29	3
SU80CY	1/6	8.0	S	RSCR	87	102	125	139	164	209	270	106	1.65	1.29	4
SZ55CY	1/9	5.5	S	RSCR	41	49	65	75	90	115	142	57	1.72	1.34	3
SZ60CY	1/8	6.0	S	RSCR	52	67	87	95	119	148	183	72	1.75	1.37	3
SZ75CY	1/7	7.5	S	RSCR	65	79	104	120	134	171	216	91	1.72	1.34	3

L系列 L Series

L66CY	1/8	6.6	S	RSIR	58	73	101	110	130	161	200	83	1.25	0.98	
L66CYA	1/8	6.6	S	RSIR	56	72	94	105	127	156	195	80	1.45	1.13	
L68CY	1/6	6.8	S	RSIR	68	87	108	125	150	188	246	95	1.41	1.10	

型号 Model	马力 Power	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量Cooling Capacity								COP(with PTC)		运行电容Run Capacitor
					ASHRAE							CECOMAF	ASHRAE	CECOMAF	
					-35	-30	-25	-23.3	-20	-15	-10	-25	-23.3	-25	
HP	cm <sup>3</sup>				w	w	w	w	w	w	w	w/w	w/w	μF	

LBP

220V-240V 50HZ R600a

L系列 L Series

L76CY	1/6+	7.6	S	RSIR	90	105	129	142	170	215	278	108	1.41	1.10	
L88CY	1/5	8.8	S	RSIR	98	115	143	155	190	238	308	118	1.40	1.09	
LK76CY	1/6+	7.6	S	RSCR	90	105	129	142	170	215	278	108	1.58	1.23	4
LK88CY	1/5	8.8	S	RSCR	98	115	143	158	190	238	308	122	1.58	1.23	5
LU43CY	1/14	4.3	S	RSCR	38	48	64	66	88	114	149	50	1.55	1.21	3
LU60CY	1/8	6.0	S	RSCR	56	72	94	105	127	156	195	80	1.60	1.25	3
LU68CY	1/6	6.8	S	RSCR	70	88	109	128	153	189	248	97	1.60	1.25	3
LU76CY	1/6	7.6	S	RSCR	90	105	128	142	170	215	278	108	1.65	1.29	4
LU88CY	1/5	8.8	S	RSCR	98	115	143	158	190	238	308	120	1.66	1.29	5
LU100CY	1/4	10.0	S	RSCR	108	126	162	170	207	252	311	136	1.65	1.29	4
LU111CY	1/4	11.1	S	RSCR	110	130	168	185	210	260	315	141	1.65	1.29	4
LZ60CY	1/8	6.0	S	RSCR	56	72	94	105	127	156	195	80	1.75	1.37	3
LZ68CY	1/6	6.8	S	RSCR	72	89	116	128	155	198	252	97	1.80	1.40	3
LZ76CY	1/6+	7.6	S	RSCR	90	106	132	150	175	222	293	114	1.80	1.40	3
LZ88CY	1/5	8.8	S	RSCR	102	121	152	162	198	250	320	125	1.80	1.40	4
LZ100CY	1/4	10.0	S	RSCR	108	126	162	170	207	252	311	136	1.75	1.37	4
LZ111CY	1/4	11.1	S	RSCR	110	130	168	185	210	260	315	141	1.75	1.37	4
LM60CY	1/8	6.0	S	ESCR	56	72	94	98	127	156	195	74	1.84	1.44	3
LM68CY	1/6	6.8	S	ESCR	72	89	116	120	155	198	252	91	1.84	1.44	3
LM76CY	1/6+	7.6	S	ESCR	90	106	132	138	175	222	293	105	1.84	1.44	3
LM88CY	1/5	8.8	S	ESCR	102	121	152	165	198	250	320	125	1.84	1.44	4
LJ60CY	1/7	6.0	S	ESCR	56	72	94	100	127	156	195	76	1.88	1.47	3
LJ68CY	1/6	6.8	S	ESCR	72	89	116	120	155	198	252	91	1.88	1.47	3
LJ76CY	1/6	7.6	S	ESCR	90	106	132	138	175	222	293	105	1.88	1.47	3
LJ88CY	1/5	8.8	S	ESCR	102	121	152	165	198	250	320	125	1.88	1.47	4

型号 Model	马力 Power	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量Cooling Capacity							COP(with PTC)		运行电容Run Capacitor	
					ASHRAE							CECOMAF	ASHRAE		CECOMAF
					-35	-30	-25	-23.3	-20	-15	-10	-25	-23.3		-25
	HP	cm <sup>3</sup>			w	w	w	w	w	w	w	w	w/w	w/w	μF

LBP

220V-240V 50HZ R600a

L系列 L Series

LJ111CY	1/6	11.1	S	RSCR	119	146	181	185	229	281	332	142	1.85	1.44	4
LR58CY	1/7	5.8	S	ESCR	46	64	85	95	116	148	188	71	1.93	1.51	2.5
LR76CY	1/6	7.6	S	ESCR	73	90	118	130	158	202	258	99	1.93	1.51	3
LR82CY	1/6+	8.2	S	ESCR	83	99	125	145	189	230	302	112	1.93	1.51	3
LH60CY	1/8	6.0	S	ESCR	56	72	94	100	127	156	195	78	1.96	1.53	1.5
LH68CY	1/6	6.8	S	ESCR	72	89	116	123	155	198	252	93	2.00	1.56	1.5
LH76CY	1/6+	7.6	S	ESCR	90	106	132	140	175	222	293	106	2.03	1.58	2.5
LV60CY	1/8	6.0	S	ESCR	54	71	93	98	126	155	194	74	2.05	1.60	1.5

QD系列 QD Series

QD100Y	1/4	10.0	S	RSIR	110	130	168	170	210	260	315	129	1.38	1.08	
QD123Y	1/4	12.3	S	RSIR	118	145	180	184	227	279	330	140	1.42	1.11	
QD135Y	1/3-	13.5	S	RSIR	123	152	187	215	232	282	340	163	1.42	1.11	
QD100YG	1/4	10.0	S	RSCR	110	130	168	180	210	260	315	137	1.70	1.33	5
QD135YG	1/3-	13.5	S	RSCR	123	150	187	220	234	282	342	167	1.58	1.23	5
QD153YG	1/3	15.3	F1	RSCR	147	181	219	246	266	316	370	187	1.58	1.23	5
QD100YU	1/4	10.0	S	RSCR	110	130	168	180	210	260	315	137	1.70	1.33	5
QD123YU	1/4	12.3	S	RSCR	118	145	180	195	227	279	330	148	1.68	1.31	5
QD135YU	1/3-	13.5	S	RSCR	123	152	187	220	232	282	340	167	1.68	1.31	5
QD153YU	1/3	15.3	F1	RSCR	147	181	219	248	266	316	370	188	1.68	1.31	5
QD167YU	3/8	16.7	F1	RSCR	169	199	236	270	280	334	391	205	1.65	1.29	6
QD100YZ	1/4	10.0	S	RSCR	110	130	168	185	210	260	315	141	1.80	1.40	4
QD123YZ	1/4	12.3	S	RSCR	118	145	180	195	227	279	330	148	1.80	1.40	5
QD135YZ	1/3-	13.5	S	RSCR	123	152	187	220	232	282	340	167	1.80	1.40	5
QD153YZ	1/3	15.3	F1	RSCR	147	181	219	250	266	316	370	190	1.78	1.39	6
QD123YJ	1/4	12.3	S	ESCR	118	145	180	195	227	279	330	148	1.85	1.44	5
QD135YJ	1/3-	13.5	S	ESCR	122	150	184	215	226	275	333	164	1.85	1.44	5

型号 Model	马力 Power	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量Cooling Capacity								COP (with PTC)		运行电容Run Capacitor
					ASHRAE							CECOMAF	ASHRAE	CECOMAF	
					-35	-30	-25	-23.3	-20	-15	-10	-25	-23.3	-25	
HP	cm <sup>3</sup>				w	w	w	w	w	w	w	w/w	w/w	μF	

LBP

220V-240V 50HZ R600a

QD系列 QD Series

QD153YJ	1/3	15.3	F1	ESCR	146	180	217	248	261	311	364	189	1.85	1.44	5
QD100YT	1/5+	10.0	S	ESCR	110	130	168	190	210	260	315	144	1.90	1.48	2.5
QD135YT	1/3-	13.5	F1	ESCR	128	159	189	230	238	288	351	175	1.90	1.48	3

LBP

110V 50HZ-60HZ R600a

DG40AY	1/11	4.0	S	RSIR	29	36	48	65	85	108	135	49	1.35	1.05	
S53AY	1/9	5.3	S	RSIR	54	63	72	85	105	131	165	70	1.55	1.21	
S75AY	1/6+	7.5	S	RSIR	88	100	127	138	168	213	272	105	1.53	1.19	
L60AY	1/7	6.0	S	RSIR	62	76	99	115	130	160	201	87	1.40	1.09	

LBP

220V-240V 50HZ R600a

变频压缩机 Frequency Conversion compressor

LU68PY*	1/6	6.8	S	BLDC	72	89	116	120	155	198	252	91	1.81	1.41	
LU76PY*	1/6+	7.6	S	BLDC	90	106	132	140	175	222	293	106	1.81	1.41	
LU88PY*	1/5	8.8	S	BLDC	102	121	152	160	198	250	320	122	1.81	1.41	
QD135PY*	1/3+	13.5	S	BLDC	123	150	187	220	234	282	342	167	1.81	1.41	

注: \*变频压缩机是在3000rpm/min的条件下测试. PS: Test of frequency conversion compressor was conducted at 3000rpm. △:S系列改进型,供选择.S Series Advanced ,For Select.